

Closed-End Wire Connectors

- Polyamide (PA), UL 94V-2 flame retardant shell rated at 105°C (221°F).
- Two types of sleeves, aluminum or tin-plated copper, to choose from.
- Long neck provides much more secure and easier installation.
- Ideal for applications requiring vibration resistance.
- UL 486C Listed and CSA C22.2 No. 188 Certified.
- Crimping tools are available upon request.



Dimensions (mm)	Cat. No.	Sleeve	Color	Electrical Ratings & Wire Range (Cu)	Approvals	Packing
	CE1	Cu	Nature	300V Max. 105°C (221°F) 22-18 AWG, Str (CE1) 24-18 AWG, Str (CE1X) Max. 2 #20 w/1 #18 Min. 2 #22	 	Carton of 30,000 (30 bags, 1,000 ea.)
	CE1X	Al				
	CE2	Cu	Nature	300V Max. 105°C (221°F) 22-14 AWG Max. 4 #18 Min. 2 #22	 	Carton of 20,000 (20 bags, 1,000 ea.)
	CE2X	Al				
	CE3X	Al	Nature	300V Max. 105°C (221°F) 18-12 AWG, Str Max. 2 #16 w/1 #12 Min. 3 #18	 	Carton of 20,000 (20 bags, 1,000 ea.)
	CE5	Cu	Nature	300V Max. 105°C (221°F) 22-10 AWG, Str (CE5) 20-12 AWG (CE5X) Max. 1 #18 w/1 #16 w/2 #14 (CE5) 3 #14 (CE5X) Min. 2 #22 w/2 #18 (CE5) 3 #18 (CE5X)	 	Carton of 10,000 (10 bags, 1,000 ea.)
	CE5X	Al				
	CE8	Cu	Nature	300V Max. (UL) 600V Max. (CSA) 105°C (221°F) 16-10 AWG, Str Max. 2 #16 w/1 #10 Min. 2 #16 w/1 #12	 	Carton of 6,000 (12 bags, 500 ea.)