



Lever Wire Connectors

- Polycarbonate (PC) and Polyamide (PA), UL 94V-0 flame retardant shell rated at T85 (IEC), 105°C (UL).
- Spring force connector constructed from tinned copper plate and stainless spring steel.
- No tools required, just push the orange levers to 90° and insert conductors and then put the levers back in place.
- Accept any combination of solid, stranded and flexible conductors from 0,2 mm²/28 AWG up to 4,0 mm²/12 AWG.
- Clear shell gives visual verification of connection.
- IEC/EN 60998 Certified and UL 486C Listed.



Dimensions (mm)	Cat. No.	Colors	Electrical Ratings & Wire Range (Cu)	Approvals	Packing
	PC622	Orange + Clear	32A, 450V, T85°C 2 x 0,2-4 mm ² , Rigid/Flex 600V, 105°C (221°F) 28-14 AWG, Sol/Str 12 AWG, Sol	CE   	Box of 100 Carton of 5,000 (10 bags, 500 ea.)
	PC623	Orange + Clear	32A, 450V, T85°C 3 x 0,2-4 mm ² , Rigid/Flex 600V, 105°C (221°F) 28-14 AWG, Sol/Str 12 AWG, Sol	CE   	Box of 100 Carton of 5,000 (10 bags, 500 ea.)
	PC625	Orange + Clear	32A, 450V, T85°C 5 x 0,2-4 mm ² , Rigid/Flex 600V, 105°C (221°F) 28-14 AWG, Sol/Str 12 AWG, Sol	CE   	Box of 50 Carton of 3,000 (10 bags, 300 ea.)

