






mini Pro Push-In Wire Connectors

-

Dimensions (mm)	Cat. No.	Colors	Electrical Ratings & Wire Range (Cu)	Approvals	Packing
	PC212	Red + Clear	24A, 450V, T85°C 2 x 0,5-2,5 mm², Rigid	CE  cec	Box of 100
			600V, 105°C (221°F) 22-12 AWG, Sol 22-14 AWG, Tin bonded Str	c 	Carton of 10,000 (10 bags, 1,000 ea.)
	PC213	Orange + Clear	24A, 450V, T85°C 3 x 0,5-2,5 mm², Rigid	CE  cec	Box of 100
			600V, 105°C (221°F) 22-12 AWG, Sol 22-14 AWG, Tin bonded Str	c 	Carton of 10,000 (10 bags, 1,000 ea.)
	PC214	Yellow + Clear	24A, 450V, T85°C 4 x 0,5-2,5 mm², Rigid	CE  cec	Box of 100
			600V, 105°C (221°F) 22-12 AWG, Sol 22-14 AWG, Tin bonded Str	c 	Carton of 5,000 (10 bags, 500 ea.)
	PC215	Grey + Clear	24A, 450V, T85°C 5 x 0,5-2,5 mm², Rigid	CE  cec	Box of 100
			600V, 105°C (221°F) 22-12 AWG, Sol 22-14 AWG, Tin bonded Str	c 	Carton of 5,000 (10 bags, 500 ea.)
	PC216	Purple + Clear	24A, 450V, T85°C 6 x 0,5-2,5 mm², Rigid	CE  cec	Box of 100
			600V, 105°C (221°F) 22-12 AWG, Sol 22-14 AWG, Tin bonded Str	c 	Carton of 5,000 (10 bags, 500 ea.)