

Winged Wire Connectors

- Tough thermoplastic, UL 94V-2 flame retardant shell rated at 105°C (221°F).
- Zinc-plated square wire spring ensures a firm grip on conductors.
- Swept-back wing design provides finger-tip comfort and increases torquing power.
- Color-coded to industry standards for quick size identification.
- Rated to 600V max. building wiring and 1000V max. signs or luminaires.
- UL 486C Listed and CSA C22.2 No. 188 Certified.
- Available in socket tools for easy installation of the connectors (See page 13).



Dimensions (mm)	Cat. No.	Color	Electrical Ratings & Wire Range (Cu)	Approvals	Packing
	P11V	Yellow	600V Max. 105°C (221°F) 10-18 AWG Max. 3 #12 Min. 2 #18	 	Box of 100 Carton of 5,000 (10 bags, 500 ea.)
	P12	Tan	600V Max. 105°C (221°F) 8-22 AWG Max. 4 #12 Min. 3 #22 Sol	 	Box of 100 Carton of 5,000 (10 bags, 500 ea.)
	P13	Red	600V Max. 105°C (221°F) 6-22 AWG Max. 4 #10 Min. 1 #18 w/1 #22	 	Box of 100 Carton of 5,000 (10 bags, 500 ea.)
	P15	Grey	600V Max. 105°C (221°F) 8-18 AWG Max. 3 #10 Min. 3 #14 w/1 #18	 	Box of 50 Carton of 2,500 (10 bags, 250 ea.)
	P17	Blue	600V Max. 105°C (221°F) 6-14 AWG Max. 3 #8 w/1 #12 Min. 3 #12	 	Box of 50 Carton of 1,500 (15 bags, 100 ea.)

*The equivalent IEC wire range is given in the appendix (See page 51).

